


# 14NDL88

**8Ω****LF Drivers - 13.5 Inches**




- 1400 W continuous program power capacity
- 88 mm (3.5 in) aluminium voice coil
- 45 - 3000 Hz response
- 99 dB sensitivity
- Ventilated voice coil gap for reduced power compression
- Aluminium demodulating ring allows a very low distortion figure
- Double silicone spider for optimized compliance



The NDL88 series is perfectly balanced for the loudspeaker systems of today. Incorporating a high temperature neodymium magnet inside the 3.5" (88mm) voice coil reduces the amount of steel needed in the motor structure, saving cost and weight. Unexpected low frequency output and midrange extension to meet with almost any driver for two way applications is the hallmark of this new performance-oriented woofer line from B&C Speakers. Do more, with less, with the NDL88 series.

# 14NDL88

LF Drivers- 13.5 Inches



Model: 14NDL88  
 Enclosure Type: Box Reflex Configuration: One Driver  
 Internal Net Volume (liters): 75 Q<sub>ts</sub>: 6  
 Tuning Frequency (Hz): 53 Port Area (cm<sup>2</sup>): 222.3  
 Frequency (-2 dB) (Hz): 53.6 Port Length (cm): 17.0  
 Frequency (-10 dB) (Hz): 41.6

## SPECIFICATIONS

Nominal Diameter	359 mm (14.0 in)
Nominal Impedance	8 Ω
Minimum Impedance	6.5 Ω
Nominal Power Handling <sup>1</sup>	700 W
Continuous power handling <sup>2</sup>	1400 W
Sensitivity (1W/1m) <sup>3</sup>	99.0 dB
Frequency Range	45 - 3000 Hz
Voice Coil Diameter	88 mm (3.5 in)
Winding Material	Aluminium
Former Material	Glass Fibre
Winding Depth	21.0 mm (0.85 in)
Magnetic Gap Depth	10.0 mm (0.4 in)
Flux Density	1.15 T

## DESIGN

Surround Shape	Triple Roll
Cone Shape	Exponential
Magnet Material	Neodymium Inside Slug
Spider	Double Silicone
Pole Design	T-Pole
Woofer Cone Treatment	WP Waterproof Front Side
Recommended Enclosure	75.0 dm <sup>3</sup> (2.65 ft <sup>3</sup> )
Recommended Tuning	53 Hz

## PARAMETERS<sup>4</sup>

Resonance Frequency	45 Hz
Re	5.0 Ω
Qes	0.31
Qms	7.8
Qts	0.3
Vas	102.0 dm <sup>3</sup> (3.6 ft <sup>3</sup> )
Sd	707.0 cm <sup>2</sup> (109.6 in <sup>2</sup> )
η <sub>o</sub>	2.9 %
X <sub>max</sub>	± 8.0 mm
X <sub>var</sub>	± 9.5 mm
M <sub>ms</sub>	86.0 g
Bl	19.9 Txm
Le	1.2 mH
EBP	145 Hz

**MOUNTING AND SHIPPING INFO**

Overall Diameter	359 mm (14.1 in)
Bolt Circle Diameter	343 mm (13.5 in)
Baffle Cutout Diameter	323.0 mm (12.72 in)
Depth	167 mm (6.57 in)
Flange and Gasket Thickness	12 mm (0.47 in)
Air Volume Occupied by Driver	3.5 dm <sup>3</sup> (0.12 ft <sup>3</sup> )
Net Weight	5.3 kg (11.68 lb)
Shipping Units	1
Shipping Weight	6.6 kg (14.55 lb)
Shipping Box	425x425x224 mm (16.73x16.73x8.82 in)

**SERVICE KIT**

Recone kit	RCK14NDL888
------------	-------------

1. 2 hours test made with continuous pink noise signal within the range Fs-10Fs. Power calculated on rated minimum impedance. Loudspeaker in free air.
2. Power on Continuous Program is defined as 3 dB greater than the Nominal rating.
3. Applied RMS Voltage is set to 2.83 V for 8 ohms Nominal Impedance.
4. Thiele-Small parameters are measured after a high level 20 Hz sine wave preconditioning test.