


- 220 W continuous program power capacity
- 2" horn throat diameter
- 75 mm (3 in) aluminium voice coil
- Titanium diaphragm
- 800 - 18000 Hz response
- 109.5 dB sensitivity
- Neodymium magnet assembly with shorting copper cap

The DE885TN is the latest version of our premium 75mm (3.0 in) voice coil, neodymium high frequency driver. The diaphragm in this model has been completely redesigned to incorporate a bent edge voice coil former, new dome and surround geometry and an optimized phase plug. These modifications combine to better control diaphragm displacement and deformations, resulting in lower distortion and a smoother higher frequency response above 10kHz.



SPECIFICATIONS

Driver mounted on B&C ME60 horn

Throat Diameter	50 mm (2 in)
Nominal Impedance	16 Ω
Minimum Impedance	10.4 Ω
Nominal Power Handling	110 W 2 hour test made with continuous pink noise signal within the range from the recommended crossover frequency to 20 kHz. Power calculated on rated minimum impedance.
Continuous Power Handling	220 W Power on Continuous Program is defined as 3 dB greater than the Nominal rating.
Sensitivity	109.5 dB Applied RMS Voltage is set to 4 V for 16 ohms Nominal Impedance.
Frequency Range	0.8 kHz - 18 kHz
Recommended Crossover	1 kHz 12 dB/oct. or higher slope high-pass filter.
Voice Coil Diameter	75 mm (3 in)
Winding Material	Aluminium
Inductance	0.1 mH
Flux Density	1.85 T
Diaphragm Material	Titanium

SERVICE KITS

HF replacement-diaphragm	MMD3DTN16M
--------------------------	------------

MOUNTING AND SHIPPING INFO

Four M6 holes 90° on 102 mm (4 in) diameter

Overall Diameter	124 mm (4.88 in)
Depth	88 mm (3.46 in)
Net Weight	2.4 kg (5.29 lb)
Shipping Units	1 pcs
Shipping Weight	2.47 kg (5.45 lb)
Shipping Box	135x135x93 mm (5.31x5.31x3.66 in)