ME464

SPECIFICATIONS

Horn mounted on B&C DE 750 compression driver.

Throat Diameter	**36 mm (1.4 in)**
Nominal Coverage Horizontal	**80 °**
Nominal Coverage Vertical	**60 °**
Cutoff Frequency	**0.3 kHz**
Material	**Polyurethane**
Design	**Constant Directivity**
Dimensions	**575x505x460 mm (22.64x19.88x18.11 in)**

MOUNTING AND SHIPPING INFO

Baffle Cutout Dimension	**538 mm (21.18 in)**
Air Volume Occupied by Driver	**35.5 dm^3 (1.25 ft^3)**
Net Weight	**4.75 kg (10.47 lb)**
Shipping Units	**1 pcs**
Shipping Weight	**7.66 kg (16.89 lb)**
Shipping Box	**610x533x508 mm (24.02x20.98x20.00 in)**

- 1.4" throat entry
- 80° x 60° nominal coverage
- Constant Directivity
- Excellent loading down to 300 Hz
- revised 20/10/20

Built to extract the full capabilities of our wide-bandwidth ring radiator drivers, B&C's new ME464 is the largest commercially available horn for professional audio. The 22” (575mm) wide mouth loads an attached driver to 300Hz, and the 1.4” throat stabilizes a 80° x 60° polar pattern to the upper limit of human hearing. Made of durable and non-resonant polyurethane, the ME464 can stand up to road use as well as shine in high output arrays in fixed installation. Reduced inter-box interaction and off axis energy from the tight pattern brings immediate benefits to sound quality and clarity, and the ME464 is the only horn which can support the full frequency response of our DCX464 coaxial driver. The ME464 can be easily applied to the DCX464 using the FB468 crossover, which is available in 8 or 16 Ohm configurations.

B&C Speakers S.p.A. Via Poggiomoro, 1 - Loc. Vallina, 50012 Bagno a Ripoli (FI) | ITALY
Tel. +39 055 65721 | Fax +39 055 6572312 | mail@bcspeakers.com

ME464





B&C Speakers S.p.A. Via Poggiomoro, 1 - Loc. Vallina, 50012 Bagno a Ripoli (FI) | ITALY
Tel. +39 055 65721 | Fax +39 055 6572312 | mail@bcspeakers.com

ME464


Horizontal
Level (dB)
0°
+30°
-30°
+60°
-60°
+90°
-90°
+120°
-120°
+150°
-150°
+/-180°
(deg)
-6
-12
-18
-24
-30
-36
-42
500 Hz
16 kHz
8 kHz
4 kHz
2 kHz
1 kHz


Vertical
Level (dB)
0°
+30°
-30°
+60°
-60°
+90°
-90°
+120°
-120°
+150°
-150°
+/-180°
(deg)
-6
-12
-18
-24
-30
-36
-42
500 Hz
16 kHz
8 kHz
4 kHz
2 kHz
1 kHz

ME464


R76.50
∅36
R76.50
∅6.50(x4)
∅102
160
487
160
R76.50
R76.50
195
195
∅6.60 (x12)
557


460
505
470


575
538


R92.50
R92.50
R92.50
R92.50